


RFoF calibration status

(Radio Freq. Over Fiber)

Hikaru Isoba
Chiba University



What was done



Calibration


1. Optical cable system
(patch cable/ optical fiber)
2. Zonu Tx/Rx
3. DTM - OF - FOAM

Integration/assembly

- Patch cable->Opt fiber
- Zonu combination
- DTM construction (4#)

Optical system

Optical system




Measured parameters


- Return Loss
- Splice Loss
- Attenuation







Optical system



- OTDR measures the back light power as a function of distance
- Peak show optical connections




Patch Cable/OF



| Loss | Number |
|---------------|--------|
| < -55[dB] | 125 |
| -55 ~ -54[dB] | 1 |
| -54 ~ -53[dB] | 0 |
| -53 ~ -50[dB] | 0 |
| > -50[dB] | 2 |

| Loss | Number |
|---------------|--------|
| < -55[dB] | 107 |
| -55 ~ -54[dB] | 14 |
| -54 ~ -53[dB] | 5 |
| -53 ~ -50[dB] | 0 |
| > -50[dB] | 2 |


Optical Fiber Attenuation



- Attenuation while the light transmit through the fiber 200m are small.

Zonu


Zonu Measurement Set Up



ZONU

Rx

Tx/Rx link with fixed Tx




Most of them have the expected profile

4 have this gain profile

- All worked as expected

Tx


Tx/Rx link with fixed Rx



DTM assembly and calibration



Full RoF system Measurement

~~Antenna + LNA~~ + DTM+Optical Fiber+FOAM



- DTM : Using new one
- FOAM : Using old power board, new PC and Rx



Status of DTM assembly



- No problem with the assembly
- 4 DTM are already build
- Have the component for 2 more stations

Gain of “DTM - Fiber - FOAM”


~~Antenna + LNA~~ + DTM + Optical Fiber+FOAM




- All CH gain between 14[dB]~19[dB] .

Temperature dependence

**DTM - FIBER -FOAM
in freezer**



**DTM - FIBER
in freezer
FOAM at room temp**



Conclusion/status/questions

- **Conclusion**



- The component for DTM/Optical fiber construction were tested (4 bonus broken)
- 4 DTM were constructed, calibrated, temp. dependence quickly checked
- We can assemble 3 stations in total

- **Questions**

- Noise measurement: Is there any other solution than buying at noise meter ?
- Any idea for the EM isolation measurement
- What is the calibration process Chiba-Madison-South Pole ?

Back up

Effect of Fiber connection cleaning



For female connector


For male connector

Cleaning : Procedure




Rotate cleaner
same direction
3 times

1 connector, 1 cleaner




Push once



Same
type


PC

OF




PC

Cleaning : Notes



- If there are some dirt on fiber surface, Return Loss will be *like* Event 4 or 5.
- Even with the cleaner, sometimes you cannot remove dirt. → look surface carefully with eyes.


The variation due to cleaning.



- Variation is slightly increase.
- Important thing is to clean at the beginning.

Temperature dependence

**DTM - FIBER -FOAM
in freezer**



**DTM - FIBER
in freezer
FOAM at room temp**

